



MORE FLEXIBILITY WITH SMARTER FEATURES

3인치 POS용 영수증 프린터
SRP-350III



주요특징



우수한 프린팅 성능

- 최고 250mm/sec 인쇄속도 (SRP-350 II 대비 25% 속도 향상)
- 4가지 타입의 디더링 그래픽 인쇄
- 스테디셀러인 SRP-350 라인의 신제품



다양한 인터페이스 지원

- USB 기본, Serial / Parallel / Ethernet 선택



사용자 중심의 디자인

- 용지 걸림 방지 가이드 (Anti-jam)
- 벽걸이형으로 공간 절약 가능
- 2인치, 3인치 용지 선택



BIXOLON[®]
a Better Solution for your Business™

3인치 POS용 영수증 프린터 SRP-350III



제품사양

Print Characteristics	
Print Method	Direct Thermal
Print Speed	SRP-350III: 250 mm/sec, SRP-352III: 230 mm/sec
Print Resolution	SRP-350III: 180 dpi, SRP-352III: 203 dpi
Print Width	Up to 72 mm
Sensor	Paper End, Paper Near End, Cover Open
Media Characteristics	
Media Type	Receipt
Media Width	80 mm Optional 58 mm (with 2 inch Partition)
Media Roll Diameter	Up to 83 mm
Media Thickness	0.062 ~ 0.075 mm
Supply Method	Easy Paper Loading
Physical Characteristics	
Dimensions (WxLxD)	145 x 204 x 146 mm (5.70 x 8.03 x 5.74 inch)
Weight	1.55 kg (3.41 lbs)
Power	EnergyStar Certified, External Power Adaptor 100-240V AV, 50/60Hz
Drawer Port	2 ports (via y-type adaptor)
Performance Characteristics	
Memory	64 Mbit SDRAM, 32 Mbit FlashROM
NV Image Memory	256 Kbytes (mono)
Receive Buffer	4 Kbytes
User Define Buffer	12 Kbytes
Interface	Dual Interface : USB V2.0 FS + Serial USB V2.0 FS + Parallel USB V2.0 FS + Ethernet
Environment Characteristics	
Temperature	Operating: 0 ~ 45°C (32 ~ 113°F) / Storage: -20 ~ 60°C (-4 ~ 140°F)
Humidity	Operating: 10 ~ 80% RH / Storage: 10 ~ 90% RH
Reliability	
Printer Unit (MCBF)	70 Million Lines
Thermal Print Head (TPH)	150 km
Auto Cutter	1.8 Million Cuts
Software	
Emulation	BXL / POS
Driver / Utility	Windows Driver, OPOS Driver, JPOS Driver, Linux CUPS Driver, Mac Driver, Virtual COM USB/Ethernet Driver, Utility Program
SDK	iOS SDK, Android SDK
Fonts / Graphics / Symbologies	
Character Size	Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24 KOR, CHN, JPN: 24 x 24
Characters Per Line	SRP-350III: Font A: 42 Font B, C: 56 KOR, CHN, JPN: 21 / SRP-352III: Font A: 48 Font B, C: 64 KOR, CHN, JPN: 24
Character Sets	Alphanumeric: 95 / Extended Graphics: 128 x 37 page / International: 32
Graphics	Supporting user-defined fonts, graphics, formats, and logos
Barcode Symbologies	1D: Codabar, Code 39, Code 93, Code 128, EAN-8, EAN-13, ITF, UPC-A, UPC-E 2D: Data Matrix, PDF417, QR code

